FIBTECH SPLICING MACHINE

Backed With
Unparalleled
Service &
Support

Loyalty Privilege



- **❖ FAST: 7 SECOND SPLICE ❖ 1 SECOND FAST BOOT ❖ ULTRA-LOW SPLICE LOSS**
- ❖ 6 MOTORS CORE ALIGNMENT SYSTEM ❖ LONG LIFE ELECTRODES-5000 SPLICES
- ❖ HIGH CAPACITY BATTERY FOR 250+ SPLICE ❖ SMALL, LIGHT WEIGHT & BEAUTIFUL
- **❖ LOW MAINTENANCE COST ❖ DUST/SHOCK/RAIN PROTECTED**
- ❖ SUPERIOR HIGH PRECISION CLEAVER ❖ METALLIC GEARS FOR LONG PRODUCT LIFE
- ❖ SUPPORT LOOSE TUBE FIBER SPLICING ❖ AIRCRAFT GRADE CONSTRUCTION MATERIAL

FAST FUSION SPLICER

SPECIFICATIONS

SPECIFICATIONS		
Applicable Fibers	Single / SMF(G.652/652D), MMF(G.651), DSF(G.653), NZDSF(G.655), G657A, G657B etc.	
Cladding Dia./Sheath Dia.	80-150μm / 100-1000um	
Cleave Length	5mm to 16mm	
Splice Programs	Stored 40 Programs & 80 snoitpO elbarug noC-	
Average Splice Loss	0.02dB (SM),0.01dB(MM),e8.04dB(DS) and 0.04dB(NZDS)	
Tube Heating Time	Typical 17sec, Slim 60mm, Slim 40mm Coating dia. 250um	
Splice Time	7 Sec (Fast Mode)	
Splice Loss Evaluation	Available	
Tensile Test	2.25N	
Screen	2 CMOS Camera with 4.3 inch Color LCD Non Touch for Fast Response	
Optical Magnification	X/Y dna X htob ro noitac ingaM Y 270X noitac	
Power Supply Included	12V Car Power Supply	
Battery Usage	Typical Operating 250 (splice / heat shrink) on a Single Charge 3h	
Result Storage	Last 10000 Records	
Electrode Life	5000 splices	
Data Interface	USB2.0, PC Software Upgrade / Data Management	
Operating Condition	Altitude: 0 to 5,000m above sea level, Wind: 15m/sec	
	Temperature: 10 to 50 deg C, Humidity: 0 to 95%RH, non-dew	
Weight	1.54kg (Without Battery), 1.82kg (Including Battery)	
Size	150D×130W×126H(mm)	
Weather Protection	Shock Resistance, Dust Resistance and Rain Resistance	
	·	

STANDARD PACKAGE

DESCRIPTION	QUANTITY
Optical Fiber Fusion Splicer	1 pc.
AC PowerAdapter/Charger	1 pc.
Battery Pack	1 pc.
High Precision Fiber Cleaver	1 pc.
Alcohol Dispenser	1 pc.
Fiber Stripper	1 pc.
Spare Electrodes	1 pair
Cooling Tray	1 pc.
Hard Carrying Case	1 pc.
Car Cigarette Lighter Charging Cable	1 pc.
Instruction Manual	1 pc.

