



## Specification Sheet

CSA025160

### Product Information

**Specifications:**

1. Fully DVB-C compliant
- 2.Support SD MPEG2 and MPEG4 AVC H.264
- 3.support ABV/Irdeto/Verimatrix/NSTV CAS
- 4.Auto and manually scan all available TV and radio channels
- 5.Powerful and highly effective 7-day EPG function
- 6.Multi-language menu,subtitle and audio output supported
- 7.USB 2.0 for PVR,Scheduled PVR,TIMESHIFT,software upgrade and media files playback
- 8.Support aspect ratio 16:9, 4:3,Pan&Scan,letter box.
- 9.Support parental local and Teletext
- 10.Support various media files playback

**Tuner and Demodulation parameter:**

RF input frequency: 44MHz~862MHz bandwidth:6/8MHz

Demodulation: 16, 32, 64, 128, 256 QAM

Symbol rate: 0.7 ~ 7Mbaud

Input impedance:75Ω

RF IN connector type: F-type

Flash Memory8 MB,SDRAM64 MB

Main chipset: Mstar MSD5C35



### Input and Output

Front panel: Button for power,CH+/CH-, VOL+/VOL-

- USB
- IR sensor
- LED

Back panel: RF IN

- Smart card slot
- CVBS
- DC IN

**Key Selling Features:**

- Full SD DVB-C Receiver with ABV/Irdeto/Verimatrix CA
- USB Media player
- Easy to use and attractive menu

### Accessories Included (in Price above)

- RCU
- User manual
- A/V cable
- Power adaptor
- Gift package

### Product Compliance

#### Hardware Compliance

Power Consumption	Power Voltage	Adaptor	Power Cord Length
MAX 8W	AC 100~240V	12V, 0.6A	1m

### Packaging Details

### UI IMAGE

Dimensions (mm)			
	H	W	L
<b>Unit</b>	35.0	104.0	160.0
<b>Giftbox</b>	55.0	160.0	200.0
<b>Carton</b>	300.0	340.0	420.0
Carton Quantity		Carton Weight (kgs)	
20 units		10KGS	

