

# Inotech

## IT-260 HD Encoder

IT-260 is new generation Encoder that can perform real-time encoding up to 6 programs for content re-distribution. Based on the customer needs, IT-26 can encode H.264 (also known as MPEG-4 AVC or Part 10) in HD format with ASI and IP output. Due to the newly encoding technology it adopts, it is with excellent encoding efficiency to support extremely low bit rate encoding while still keep good video quality. With ASI and IP input, IT-260 supports PID remapping and EPG data insertion and multiplexing. It not only provides a Cost-effective yet scalable solution for network operators to compress the real-time programs for content re-distribution, but provides a easy-to-use platform ready for application through IPTV or OTT.



### Features:-

- Encoding up to 6 Programs in H.264 HD Format.
- Support SDI/ HDMI Input.
- Support both ASI & IP input / output.
- MPEG-1 Layer II Audio, LC-AAC, HE-AAC & Dolby AC-3(Future Feature)
- Support CBR / VBR encoding.
- Support Stream Processing including PID remapping & EPG Data Insertion.



## Specifications:-

### Encoding

Video Encoding (CBR & VBR)	MPEG-2 MP@ML MPEG-2 MP@ML MPEG-4 AVC at MP@L3 MPEG-4 AVC at HP@L3
----------------------------	--

SDI Input	SD SDI & HD SDI with embedded Audio
-----------	-------------------------------------

HDMI Input	Compatible with HDCP
------------	----------------------

### Video Output Bit Rate (CBR & VBR)

H.264 HD	1 Mbps ~ 9 Mbps
----------	-----------------

### Video Output Resolution

HD Resolution	1920x1080i, 1280x720p
---------------	-----------------------

GOP Structure	IBP, IBBP
---------------	-----------

Audio Formats	AAC, MPEG-1 Layer II, Dolby Digital AC-3(Future)
---------------	--

### Remultiplexing

PID	Re-mapping & Filtering MPTS output Synchronisation
-----	---

Routing	Any Input to Any Output
---------	-------------------------

### IP & ASI Interface

IP Interface	1 x 1000 Mbps/port
IP Encapsulation	MPEG TS over UDP/RTP
MPEG TS	MPTS & SPTS
I/O processing	Up to 12 Streams, max @ 72Mbps / Socket

Addressing Management	Unicast & Multicast IGMPv1, IGMPv2, IGMPv3
FEC	ProMPEG
ASI Interface	4 BNC Connectors (2ASI Inputs & 2 ASI Outputs) 75Ω
MPEG Format I/O	188/204Bytes/TS
Processing	1 MPTS/SPTS/Port up to 120 Mbps/port

### Management

Interface	100BaseTX, RJ45
NMS Support	SNMP

### Physical & Environment

Input Voltage	90-260 VAC
Power Consume	Approx 60 W
Rack Space	1 RU
Dimension	480mm x 44mm x 440mm
Temp.	0 ° to 50 ° C
Humidity	<95%